

# US WEATHERSEAL WINDOWS & DOORS CORP. TEST REPORT

**SCOPE OF WORK**

AAMA/WDMA/CSA 101/I.S.2/A440 TESTING ON 2128, CASEMENT WINDOW

**REPORT NUMBER**

I1716.01-109-44

**TEST DATE(S)**

08/23/18 - 08/28/18

**ISSUE DATE**

06/21/19

**RECORD RETENTION END DATE**

08/28/22

**PAGES**

24

**DOCUMENT CONTROL NUMBER**

RT-R-AMER-Test-2804 (04/17/18)

© 2017 INTERTEK



## TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.

Report No.: I1716.01-109-44

Date: 06/21/19

### REPORT ISSUED TO

#### US WEATHERSEAL WINDOWS & DOORS CORP.

4916 3<sup>rd</sup> Avenue

Brooklyn, New York 11220

### SECTION 1

#### SCOPE

Intertek Building & Construction (B&C) was contracted by US Weatherseal Windows & Doors Corp. to perform testing in accordance with AAMA/WDMA/CSA 101/I.S.2/A440 on their 2128, Casement Window. Results obtained are tested values and were secured by using the designated test method(s). Testing was conducted at the Intertek B&C test facility in York, Pennsylvania. This report does not constitute certification of this product nor an opinion or endorsement by this laboratory.

### SECTION 2

#### SUMMARY OF TEST RESULTS

TITLE	RESULTS
AAMA/WDMA/CSA 101/I.S.2/A440	Class LC – PG40 – 914 x 1524 (36 x 60) - C
Design Pressure	±1920 Pa (±40.10 psf)
Air Infiltration	1.1 L/s/m <sup>2</sup> (0.22 cfm/ft <sup>2</sup> )
Water Penetration Resistance Test Pressure	290 Pa (6.06 psf)

Reference must be made to Intertek B&C Report No. I1716.01-109-44, dated 6/21/19 for complete test specimen description and detailed test results.

For INTERTEK B&C:

<b>COMPLETED BY:</b>	Richard E. Hartman III	<b>REVIEWED BY:</b>	Timothy J. McGill
<b>TITLE:</b>	Technician – Product Testing	<b>TITLE:</b>	Manager – Product Testing
<b>SIGNATURE:</b>		<b>SIGNATURE:</b>	
<b>DATE:</b>	06/21/19	<b>DATE:</b>	06/21/19

REH:wnl

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.

Report No.: I1716.01-109-44

Date: 06/21/19

### SECTION 3

#### TEST SPECIFICATION(S)/METHOD(S)

The specimen was evaluated in accordance with the following:

**AAMA/WDMA/CSA 101/I.S.2/A440-17**- *North American Fenestration Standard/Specification for Windows, Doors, and Skylights*

The following test methods were used during testing:

**ASTM E283-04(2012)**, *Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen*

**ASTM E330/E330M-14**, *Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference*

**ASTM E547-00(2016)**, *Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Cyclic Static Air Pressure Difference*

**ASTM E2068-00(2016)**, *Standard Test Method for Determination of Operating Force of Sliding Windows and Doors<sup>1</sup>*

**ASTM F588-17**, *Standard Test Methods for Measuring the Forced Entry Resistance of Window Assemblies, Excluding Glazing Impact*

### SECTION 4

#### MATERIAL SOURCE/INSTALLATION

Test specimen(s) was provided by the client. Representative samples of the test specimen(s) will be retained by Intertek B&C for a minimum of four years from the test completion date.

The specimen was installed into a Spruce-Pine-Fir wood buck. The rough opening allowed for a 1" shim space and the exterior perimeter of the specimen was sealed to the test buck. Installation of the tested product was performed by the Intertek B&C.

## TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.

Report No.: I1716.01-109-44

Date: 06/21/19

LOCATION	ANCHOR DESCRIPTION	ANCHOR SPACING
Jambs	2" x 2" Aluminum L-angle	3" from each corner and spaced 13-1/2" on center with one #10 x 1" hex head self-tapping screw through the clip and into the frame. One #10 x 1-1/2" pan head screw through the clip and into the wood buck
Head and sill		3" from each corner with one at the midspan with one #10 x 1" hex head self-tapping screw through the clip and into the frame. One #10 x 1-1/2" pan head screw through the clip and into the wood buck

### SECTION 5 EQUIPMENT

**Tape Measure Verification:** 63788

**Force Gauge:** INT00155

**Weather Station:** 63316

**Control Panel:** 005644

**Spray Rack:** 003956-B

**Linear Transducer:** INT00147, 65990, 65989

**Stop Watch:** INT00975

**Spring Scale:** INT00009, 63395

### SECTION 6 LIST OF OFFICIAL OBSERVERS

NAME	COMPANY
Ben Lai	US Weatherseal Windows & Doors Corp.
Ru Zhang Zhao	US Weatherseal Windows & Doors Corp.
Timothy J. McGill	Intertek B&C
Richard E. Hartman III	Intertek B&C

**TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.**

Report No.: I1716.01-109-44

Date: 06/21/19

**SECTION 7**

**TEST SPECIMEN DESCRIPTION**

**Product Type:** Casement Window

**Series/Model:** 2128

**Product Size(s):**

OVERALL AREA:	WIDTH		HEIGHT	
	millimeters	inches	millimeters	inches
1.4 m <sup>2</sup> (15.0 ft <sup>2</sup> )				
Overall size	914	36	1524	60
Vent	848	33-3/8	1457	57-3/8

**Frame Construction:**

MEMBER	MATERIAL	DESCRIPTION
Head, sill, and jambs	Aluminum	Extruded, dual-strutted, and thermally broken

	JOINERY TYPE	DETAIL
All corners	Mitered	Sealed and secured using corner keys located in the interior and exterior hollows. The keys were staked and lanced once on each side of the key.

**Vent Construction:**

MEMBER	MATERIAL	DESCRIPTION
Rails and stiles	Aluminum	Extruded, dual-strutted, and thermally broken

	JOINERY TYPE	DETAIL
All corners	Mitered	Sealed and secured using corner keys located in the interior and exterior hollows. The keys were staked and lanced once on each side of the key.

**Reinforcement:** No reinforcement was utilized.

**Weatherstripping:**

DESCRIPTION	QUANTITY	LOCATION
0.187" backed by 0.230" diameter bulb seal	1 Row	Vent, interior perimeter between vent and frame
Custom rubber gasket	1 Row	Frame, interior perimeter
0.187" backed by 0.230" diameter bulb seal	1 Row	Vent, exterior perimeter between vent and frame

## TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.

Report No.: I1716.01-109-44

Date: 06/21/19

**Glazing:** *No conclusions of any kind regarding the adequacy or inadequacy of the glass in any glazed test specimen(s) can be made.*

GLASS TYPE	INTERIOR LITE	SPACER TYPE	INTERMEDIATE LITE	SPACER TYPE	EXTERIOR LITE	GLAZING METHOD
1-5/8" IG	1/4" clear tempered	Desiccant-filled aluminum box spacer	1/4" clear tempered	Desiccant-filled aluminum box spacer	1/4" clear tempered	The glazing was set from the interior onto a vinyl glazing strip against the frame. The glazing was securing using an extruded aluminum snap-in glazing stop with a vinyl glazing strip against the glazing. Silicone was utilized along the exterior perimeter of the glazing on top of the vinyl glazing strip.

LOCATION	QUANTITY	DAYLIGHT OPENING		GLASS BITE
		millimeters	inches	
Vent	1	686 x 1295	27 x 51	1"

### Drainage:

METHOD	SIZE	QUANTITY	LOCATION
Weepslot	1-3/8" wide by 1/4" high	2	Sill, 6-1/2" from each corner, draining from the interior sill frame to the exterior

### Hardware:

DESCRIPTION	QUANTITY	LOCATION
Handle and multi-point lock assembly	1 Set	Handle located on the latch stile 28-1/2" from the bottom rail
Lock points	3	Latch jamb, 10-1/2", 37-3/4", and 49-1/4" from the sill
Limit device	1	Sill, 2-1/2" from the latch jamb
Barrel hinges	3	Hinge jamb, 9-1/2", 19", and 50-3/4" from the head

**TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.**

Report No.: I1716.01-109-44

Date: 06/21/19

**SECTION 8**

**TEST RESULTS**

The temperature range during testing was 23 - 30°C (73 - 86F). The results are tabulated as follows:

TITLE OF TEST	RESULTS	ALLOWED	NOTE
<b>Operating Force,</b> per ASTM E2068	Initiate Motion: <4 N (<1 lbf) Maintain Motion: 58 N (13 lbf) Latches: 62 N (14 lbf)	155 N (34.85 lbf) max  100 N (22.48 lbf) max  100 N (22.48 lbf) max	
<b>Air Leakage,</b> Infiltration per ASTM E283 at 75 Pa (1.57 psf)	1.1 L/s/m <sup>2</sup> (0.22 cfm/ft <sup>2</sup> )	1.5 L/s/m <sup>2</sup> (0.3 cfm/ft <sup>2</sup> ) max.	1, 2
<b>Water Penetration,</b> per ASTM E547 at 180 Pa (3.76 psf)	Pass	No leakage	3
<b>Uniform Load Deflection,</b> per ASTM E330 Deflections taken between lock points +1200 Pa (+25.06 psf) -1200 Pa (-25.06 psf)	<0.3 mm (<0.01") 0.3 mm (0.01")	Report only	4, 5, 6
<b>Uniform Load Structural,</b> per ASTM E330 Permanent set taken between lock points +1800 Pa (+37.59 psf) -1800 Pa (-37.59 psf)	0.3 mm (0.01") 0.5 mm (0.02")	2.8 mm (0.11") max. 2.8 mm (0.11") max.	5, 6
<b>Forced Entry Resistance,</b> per ASTM F588, Type: B - Grade: 10	Pass	No entry	
<b>Sash Vertical Deflection</b> 200 N (45 lbf)	1.3 mm (0.05")	1.3 mm (0.05") max.	

**TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.**

Report No.: I1716.01-109-44

Date: 06/21/19

TITLE OF TEST	RESULTS	ALLOWED	NOTE
<b>OPTIONAL PERFORMANCE</b>			
<b>Water Penetration,</b> per ASTM E547 at 290 Pa (6.06 psf)	Pass	No leakage	3
<b>Uniform Load Deflection,</b> per ASTM E330 Deflections taken between lock points +1920 Pa (+40.10 psf) -1920 Pa (-40.10psf)	0.3 mm (0.01") 0.5 mm (0.02")	Report only	4, 5, 6
<b>Uniform Load Structural,</b> per ASTM E330 Permanent set taken between lock points +2880 Pa (+60.15 psf) -2880 Pa (-60.15psf)	0.5 mm (0.02") 0.3 mm (0.01")	2.8 mm (0.11") max. 2.8 mm (0.11") max.	5, 6

*Note 1: The tested specimen meets (or exceeds) the performance levels specified in AAMA/WDMA/CSA 101/I.S.2/A440 for air leakage resistance.*

*Note 2: Test Date 08/24/18 / Time: 9:30 AM*

*Note 3: Without insect screen.*

*Note 4: The deflections reported are not limited by AAMA/WDMA/CSA 101/I.S.2/A440 for this product designation. The deflection data is recorded in this report for special code compliance and information only.*

*Note 5: Loads were held for 10 seconds.*

*Note 6: Tape and film were not used to seal against air leakage during structural testing.*

**SECTION 9  
ALTERATIONS**

*No alterations were required.*



## TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.


Report No.: I1716.01-109-44

Date: 06/21/19

### SECTION 10

#### LOCATION OF AIR SEAL

The air seal between the test specimen and the test wall is detailed below. The seal is made of foam weatherstripping and is attached to the edge of the test specimen buck. The test specimen buck is placed against the test wall and clamped in place, compressing the weatherstripping and creating a seal.



## TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.

Report No.: I1716.01-109-44

Date: 06/21/19

### SECTION 11

#### CONCLUSION

The specimen tested successfully met the performance requirements for a **Class LC – PG40 – 914 x 1524 (36 x 60) - C** rating

Reference must be made to Intertek B&C Report No. I1716.01-109-44, dated 6/21/2019 for complete test specimen description and detailed test results.

### SECTION 12

#### PHOTOGRAPH



**Photo No. 1**  
**Test Specimen**



Total Quality. Assured.

130 Derry Court  
York, Pennsylvania 17406

Telephone: 717-764-7700  
Facsimile: 717-764-4129  
[www.intertek.com/building](http://www.intertek.com/building)

**TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.**

Report No.: I1716.01-109-44

Date: 06/21/19



**SECTION 13**  
**DRAWINGS**



The test specimen drawings have been reviewed by Intertek B&C and are representative of the test specimen(s) reported herein. Test specimen construction was verified by Intertek B&C per the drawings included in this report. Any deviations are documented herein or on the drawings.

# Window glass

**intertek**  
Total Quality. Assured.

Report #: 11716.01  
Date: 9/5/2018  
Verified by: *Richard E. H. Smith*






0808306



0808204




0808101



0808007



0808702






ITEM	2128	
PROJECT	ALUMINUM DOOR & WINDOW	
DESIGN	STARLIGHT	
CONTENT	DETAIL DWG	
ITEM MARK		
DATE	2018-1-16	
CHANGED		
No.	DATE	CONTENT

CONFIRM SIGNING:


914

1524






执手 G-46551-96-0-1  
(正装)




A-A-1




C — C








B - B





A - A





0550102









0502410





0502422







0502332




0502313



0507000




0507002



152 mm (6")

305mm (12")

152 mm (6")



3  
The installation sequence

Fixed slice  
固定片分布的位置 distribution



Total Quality. Assured.

130 Derry Court  
York, Pennsylvania 17406

Telephone: 717-764-7700  
Facsimile: 717-764-4129  
www.intertek.com/building

**TEST REPORT FOR US WEATHERSEAL WINDOWS & DOORS CORP.**

Report No.: I1716.01-109-44

Date: 06/21/19

**SECTION 14**

**REVISION LOG**

REVISION #	DATE	PAGES	REVISION
0	06/21/19	N/A	Original Report Issue